



PRIMO SUSTAINABLE PRODUCTS Product Data Sheet

Primo Classic Marmorino

Primo Classic Marmorino is an all natural green building product. It contains zero V.O.C.'s and absorbs the off gasses produced by many of the petroleum byproducts that are currently used in the building industry thereby improving indoor air quality. Lime is naturally resistant to mold and mildew and wicks moisture from the air. Upon curing, lime plasters return to their natural state, stone, which produces a long lasting and enduring finish. Primo Classic Marmorino is produced from a mixture of high quality calcium carbonate lime, crushed marble and other organic binders. Primo Classic Marmorino can be used as a base coat for Primo Lime Paint or as a stand alone product in producing textural and rustic finishes. This all natural product offers the applicator a wide range of options in producing rich and luxurious finishes. The base for this product is slaked lime putty that has been aged at least six months.

Application

Primo Classic Marmorino is applied onto drywall or existing plaster or cement substrate. We highly recommend that this product be applied over Primo Prep Coat. The Primo Prep Coat provides a surface that the Primo Classic Marmorino can adequately adhere to. Failure to follow this step could result in the finish not adhering to the surface. Primo Classic Marmorino is applied with a stainless steel trowel and can be used in one coat applications for base coats or 2-3 coat applications for use as a finished product. The standard method of application is as follows: Brush, roll or spray Primo Prep Coat on surface and let completely dry. Trowel a thin coat of Primo Classic Marmorino over surface being sure to pull tight to remove any chatter marks. Let this coat dry overnight. Apply second coat of Primo Classic Marmorino using artistic troweling technique. After this coat has absorbed the moisture, a very thin third coat may be applied and burnished. After the finish has completely dried (at least 24 hours) a coat of Primo Cera Wax Sealer may be applied for protection and to enhance the look of the finish.

All of our plaster products come untinted. We highly recommend the use of natural earth pigments to tint the plasters. Liquid universal tints can react with lime and can cause the finish not to adhere to the surface. Make sure to test for plaster adherence first if using universal tints.



Color: Naturally white in color

Flash Point: None

Composition: Calcium carbonate lime putty, marble aggregate, a proprietary mixture of other natural binders including linseed oil and olive oil

Health Hazards: Avoid continual contact with skin or eyes. Always wear safety glasses and rubber gloves when handling mixture. Prolonged contact may irritate skin. Direct eye contact can cause permanent damage to vision. Do not ingest or inhale product. If product comes in contact with skin, wash off with soap and water. If contact with eyes occurs, flush with water and contact a physician. If product is ingested, drink plenty of water and contact a physician.

Product Handling: Whenever possible contain and sweep up spillage. Product contains alkaline material. Dispose of product in accordance with Federal, State and local regulations.